

BIRD FRIENDLY FILM

- .1 Supply and install visible markers onto exterior glazed surfaces to reduce the incidence of bird collisions.
- .2 Samples for Verification: Submit two (2) samples 300mm x 300mm (12" x 12") for verification for each type and colour of bird friendly films specified in this Section prior to ordering samples from film manufacturer. Submit statements of visible markers properties indicating compliance with specified standard requirements for each type of bird friendly film.
- .3 Field Reports: Provide a building assessment for wildlife sustainability, addressing building height; glazing type; reflectivity, visibility and contrast; and surrounding area vegetation and building orientation.
- .4 Materials Manufacturer: Convenience Group Inc., 10 Butterick Road, Toronto, Ontario, Canada, M8W 3Z8; Phone: (416) 233-6900; Email: info@conveniencegroup.com; URL: www.conveniencegroup.com
- .5 Bird Friendly Film: Single layer poly vinyl chloride, 50.8 microns, with exterior permanent adhesive.
 - .1 Basis-of-Design Material:
 - .1 Horizontal visible lines, Venetian Series by Convenience Group Inc.
 - .2 Horizontal visible lines, Venetian Duotone Series by Convenience Group Inc.
 - .3 Circular visible markers, Horizon Series by Convenience Group Inc.
 - .4 Circular visible markers, Symmetry Series by Convenience Group Inc.
 - .5 Circular visible markers, Symmetry Duotone Series by Convenience Group Inc.
 - .6 Circular visible markers, Rain Series by Convenience Group Inc.
 - .7 Circular visible markers, Rain Duotone by Convenience Group Inc.
 - .8 Circular visible makers, 6mm (1/4") diameter and spaced 100mm (4") to 279mm (11") and 100mm (4") to 279mm (11"); CityScape Series by Convenience Group Inc.
 - .9 Circular visible makers, 6mm (1/4") diameter and spaced 100mm (4") to 279mm (11") and 100mm (4") to 279mm (11"); CityScape Duotone Series by Convenience Group Inc.
 - .10 [Custom Design]
- .6 Verification of Conditions: Examine glazing and surrounding adjacent surfaces for conditions affecting installation. Proceed with bird friendly film installation when ambient and substrate temperature conditions are within limits permitted by manufacturer.
- .7 Install using certified installers recommended by manufacturer, in accordance with the manufacturer's written instructions and the contract documents; plumb, true, and level over clean glazing. At completion of installation, clean all surfaces so they are free of foreign matter using cleaners recommended by material manufacturer.

END OF SECTION SHORT-FORM PRODUCT PARAGRAPH